



741A

**MORTICE LOCK,
CENTRE DISTANCE 92**

PRODUCT:

The mortice lock **741A** series with centre distance **92** can be installed on metal doors. It can be used with the wide range of Iseo cylinders, giving to the doors different security levels.

OPERATION:

The deadbolt and the latchbolt are operated by the key.
The latchbolt is operated by the handle.

RANGE:

Mechanical lateral locks, centre distance 92, with the following functions:

- Latchbolt and deadbolt (741A series)
- Roller and deadbolt (743A series)

COMPATIBLE PRODUCTS:

Adjustable and fixed striking plates
(please refer to the striking plates for Performa in the ISEO general catalogue)

STANDARDS:

EN12209:2016

TEXT FOR SPECIFICATIONS:

The narrow mortice lock 741A ISEO series for metal frames with 92 mm centre distance, latchbolt operated by handle and key, latchbolt with adjustable projection and 10 mm thickness.

ISEO®

TECHNICAL FEATURES:

92 mm centre distance
with european profile cylinders

Latchbolt operated by handle and key

**Latchbolt and deadbolt
flush with front plate**

**Deadbolt with one throw 14 mm
for backset 25, one throw 20 mm for
backset 30 and 35**

8 mm handle follower

Backsets 25, 30, 35 mm

22 mm squared front plate

Front plate in stainless steel

KEY POINT

- Reversible latchbolt with adjustable projection;
- Deadbolt with one throw 20 mm for backsets 30 and 35 mm;
- Closed case on all sides. This stops door chips and shavings from getting jammed in the lock;
- 3 fixing holes, 2 of which with backset 43 mm;
- Case painted marbled grey.

www.iseo.com