


Top Exit dgt

Motorized opening and closing system for metal frames. Panic function according to EN 1125 in conjunction with Palmo panic exit device.

Door status control for security supervision. Lockbus interface for integration with ISEO access control systems. It can be connected to alarm systems.





Push Sirena PANIC EXIT DEVICE WITH ACOUSTIC ALARM

The ideal solution for shops, small and medium warehouses. Compatible with ISEO panic exit devices of the Push series. Strong acoustic alarm (90 dB) when the bar is pressed. Powered by long life batteries with "low battery" signal. "Break" function operated by the key to exit without alarm.

rim Tronic ELECTRONIC OUTSIDE UNIT

To be used in conjunction with any panic and emergency exit devices. Access control management also by remote pulse. Permanent or temporary handle enabling. Anti-vandalism device. Signalling LED.



SEO Zero1 ELECTRONIC SOLUTIONS

A NEW RANGE OF ELECTRONIC PRODUCTS BY ISEO GROUP WHICH TOTALLY CHANGES THE WAY TO MANAGE SECURITY AND ACCESS CONTROL SYSTEMS.

Thanks to their high technology features, ISEO Zero1 products may offer comfort and ease of use. They can all be integrated and allow to manage any access in any situation, offering flexibility, smart solutions and security.



THE LATEST EVOLUTION OF ACCESS CONTROL

App available for any smartphone (iOS and Android). Suitable for ISEO Zero1 devices thanks to Bluetooth Smart technology. No need of additional hardware

plug-ins. Management of the opening authorizations. Handling of particular users' authorizations. Free software updates.



DOUBLE KNOB ELECTRONIC CYLINDER

Bluetooth module allowing to interface with smartphones and $\mbox{\rm Argo}$ $\mbox{\rm App}.$

Stand-alone access control system with RFID Multistandard credential reader and signaling LED. It can be fit with most European profile cylinder locks.

Harmless installation and replacement, with no wiring (battery-operated). Unique and innovative design, several colours and finishes available. Modular system for a simple and rapid customized configuration Heavy Duty version (IP66, IP67, IP69).

Aries SMART

ELECTRONIC TRIM SET

Bluetooth module allowing to interface
with smartphones and Argo App. Standalone access control system. It can be fit
on most doors (wood, aluminum, iron).
Harmless installation even on existing
doors (it requires 2 holes only). RFID Multistandard credential reader with signaling
LED. It works with batteries up to 40.000
operations. IP55 version for outdoor.

Stylos SMART CREDENTIAL READER

Bluetooth module allowing to interface with smartphones and Argo

App. Access control system easy
to use and to install. Ideal solution
for offices, small companies and
residential buildings. RFID Multistandard credential reader with
numerical keyboard and graphic or
LED display. Lockbus interface
for direct integration with ISEO
controllers and actuators. Encrypted data transmission and
peripherals safe authentication. IP66 version for outdoor.

FOR ARMOURED DOORS

Bluetooth module allowing to interface with smartphones and Argo App. Electromechanical opening and closing mechanism. Smart system for access control management. It can be integrated in domotic systems. Accessories can be easily combined in doors design. Lockbus interface for integration in ISEO access control management systems.

X1R SMART





9000 with Mobile validator MECHATRONIC CYLINDER

Mechanical security and electronic flexibility in a unique product. Tailor-made MK system programming. Mobile validator for key authorizations update. Registered, patented and non-duplicable key profile for a total security. Harmless installation with no cabling. It can be fit with any European profile cylinder locks.

hesis 2.0 SECURITY SOLENOID LOCK



Standard, Latchbolt, Professional and Mini versions. Normally Closed (fail secure) and Normally Open (fail safe) versions. Door status control programming for security supervision. Lockbus interface for integration with ISEO access control systems. Stand alone, manual and automatic interlock configurations. Low power consumption device with power reserve (booster).



Perfect combination of security and comfort. It operates with the most advanced access control systems. It can be set with three different options: Total, Light, Free. Acoustic opening and closing signals. Mechanical opening by handle with comfort function. It can be combined with a panic exit device for emergency exits.



Iseo Serrature s.p.a. Via San Girolamo 13 25055 Pisogne (BS) ITALY iseo@iseo.com

ISEO Zero1

ITALY

Via Don Fasola 4 I-22069 Rovellasca (CO) zero1-it@iseo.com iseozero1@iseo.com

800-728722

ELECTRONIC SUPPORT SERVICE

GERMANY

ISEO Deutschland GmbH zero1-de@iseo.com

0700-00473601

FRANCE

ISEO France s.a.s. zero1-fr@iseo.com +33 1 64835858

SPAIN

Cerraduras ISEO Ibérica S.L. zero1-es@iseo.com

900-126356

ASI

ISEO Asia Pacific SDN. BHD.

zero1-asia@iseo.com +603 80753331

ISEO Beijing zero1-cn@iseo.com +8610 58698079

UNITED ARAB EMIRATES

Iseo Projects and Access Control DMCC iseoprojects@iseo.com +971 4 5136162

SOUTH AFRICA

ISEO South Africa (Pty) LTD

zero1-za@iseo.com

ROMANIA

Feroneria Prod S.A. zero1-ro@iseo.com

iseozero1.com